



1900 Albany Place SE  
P.O. Box 286  
Orange City, IA 51041

800-747-3436 Fax 712-737-3893  
www.oldmastrs.com

## PRODUCT INFORMATION

### *H2O*<sup>®</sup> ACRYLIC SANDING SEALER

<b>PRODUCT NO.</b>	75201, 75204, 75205
<b>GENERIC TYPE</b>	Acrylic Latex Sanding Sealer
<b>COLOR</b>	Clear Gloss
<b>GLOSS</b>	90 @ 60°
<b>SOLIDS BY WEIGHT</b>	33.0%
<b>SOLIDS BY VOLUME</b>	30.0%
<b>V.O.C.</b>	335 grams/liter
<b>THEORETICAL COVERAGE @ 1 MIL DFT</b>	481 sq. ft. per gal.
<b>COVERAGE @ RECOMMENDED DFT</b>	205 to 409 sq. ft.
<b>RECOMMENDED DFT PER COAT</b>	1 to 2 Mils
<b>WEIGHT PER GALLON</b>	8.50 lbs.
<b>FLASH POINT</b>	Not applicable
<b>USE</b>	Formulated for use on new or bare interior wood surfaces. Do not use on floors.
<b>VISCOSITY AT 77°F</b>	25 sec. #4 Ford Cup
<b>AVERAGE DRY TIME AT 70°F &amp; 50% R.H.</b>	Dry to touch in 10 minutes. Sand after 30 minutes.
<b>RECOMMENDED THINNER</b>	Water
<b>APPLICATION</b>	Brush, pad, roll, or spray. When spraying, reduce with up to 1 pint water per gallon depending on equipment.
<b>SURFACE PREPARATION</b>	The surface must be clean, dry, and free of wax, oil, and grease. Remove all sanding dust with a rag dampened with water.
<b>CLEAN UP</b>	Soap and water

**FOR THE LOVE OF WOOD<sup>®</sup>**

Interior Wood Stains, Clears, Removers & Miscellaneous Sundries



## PRODUCT INFORMATION

### **H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER**

**DESCRIPTION:** OLD MASTERS<sup>®</sup> H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER is a crystal clear water reducible finish for use on new or bare interior wood surfaces, **except floors.** OLD MASTERS<sup>®</sup> technology has produced a superior product with fast dry, low odor, and good protection. Its crystal clarity produces a clear gloss finish and is recommended as a first coat or sealer prior to application of waterborne varnish or polyurethane. It does not yellow with aging when used as a protective clear coating over **waterborne stains** or light colored woods.

**THINNING:** If necessary, it may be thinned with approximately one pint of water per gallon, as needed for spray application.

**SPREADING RATE:** Recommended rate of application is 200 to 400 square feet per gallon.

**CLEAN UP:** Wash brushes and equipment in warm, soapy water and rinse with water.

**DRYING TIME:** At 50% relative humidity and 70°F, H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER will dry to touch in 10 to 15 minutes, and be ready to sand in 30 minutes.

**RECOMMENDED FINISH COAT:** Topcoat with Old Masters<sup>®</sup> H<sub>2</sub>O<sup>®</sup> ACRYLIC FINISHES.

**SURFACE PREPARATION:** All wood surfaces must be clean, dry, and free from dirt, wax, or grease. Sand the wood thoroughly with medium grit sandpaper and progress to fine grit sandpaper. Always sand in the direction of the wood grain. Sand smooth and remove dust particles with a rag dampened with water. If previously finished surfaces are to be refinished, completely remove the old finish to bare wood and follow the surface

preparation directions above. Open grained woods may be filled with a wood grain filler and sanded smooth with 220 or 400 grit paper. Make certain all dust is removed prior to application of any material.

**APPLICATION:** DO NOT SHAKE! Stir well before and during application. H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER appears milky in the can but will dry clear. It may be brushed, rolled, or sprayed. If necessary, it may be thinned with approximately one pint of water per gallon, as needed for spray application. One coat thoroughly seals and prepares the surface for succeeding coats of finish. Apply in full, even coats; if brushing, apply liberally and keep a wet edge, working quickly to insure an even coat. Large, flat surfaces may be rolled and quickly leveled off with a brush. Allow to dry at least one-half hour before sanding. Remove all sanding dust with a clean rag dampened with water, and apply desired finish coat. May be used over solvent/oil based stains provided they are completely dry before application of H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER. **Many waterborne clears may have a tendency to yellow over solvent/oil based white or pastel colored stains. Please use caution and test before you start your project.**

**HELPFUL ADVICE:** We recommend applying when air and surface temperatures are between 60°F and 90°F, and humidity is between 30% and 70%.

H<sub>2</sub>O<sup>®</sup> ACRYLIC SANDING SEALER is non-toxic and environmentally friendly.

MAX. VOC: 550 grams/liter (4.6 lbs/gal)

### CAUTION!

Do not take internally. Close container after each use.

KEEP OUT OF REACH OF CHILDREN. Protect from freezing.

Stain will not freeze, but its drying time does depend upon the surface temperature. The colder it is, the slower it dries.

### Limited Warranty

Since Old Masters<sup>®</sup> does not control the application of its products, nor the condition of the surfaces to which they are applied, a Limited Warranty is provided. If the products do not perform as specified, for whatever reason, Old Masters<sup>®</sup> liability will under no circumstances exceed replacement of the product.

OLD MASTERS<sup>®</sup>  
1900 ALBANY PLACE SE  
ORANGE CITY, IA 51041